

BOLT

Bolt is a truly versatile LED blinder, that has the ability to be mounted in 2 or 4 units linear assemble or 4 units squared assembled, using the proper accessories.

light source	1x 100W white COB LED + 1x 10W amber LED for red-shift effect
brightness	5,000 lm, 205 lux in @5m
LED scan rate	1000Hz
color rendering index	75 or 92 versions available
color temperature	3000K or 6500K or 3000-6500K versions
input voltage	100~240V AC, 50/60Hz
optics	60°
control protocol	DMX512
dimmer	0-100% (16 bits)
connections	DMX in/out, power in/out
material / color	die-cast aluminum / black
certification	CE and RoHS2
dimensions / weight	200x130x130mm / 3,5kg
cooling	convection
IP rate	IP65



X-BOLT

X-Bolt is a IP65 blinder, featuring high powered 400W white COB LEDs plus a 10W amber LED for red-shift effect, a wide 60 degree beam angle and a optional color temperature that can be 3000K or 4500K or 6500K. It comes in a unique configuration, easily attachable narrow beam filters, manual adjustable pan focus, pixel control, variable dimming curve modes and an integrated yoke and side mounting brackets.

light source	4x 100W white COB LED + 4x 10W amber LED for red-shift effect
light output	35000lm
LED scan rate	1000Hz
color temperature	3000K or 4500K or 6500K
max. power consumption	400W
input voltage	100~240V AC, 50/60Hz
optics	60 degrees
control protocol	RDM and DMX512
display	LCD menu display with 4 touch button control panel
material / color	die-cast aluminum / black
certification	CE and RoHS2
dimensions / weight	373x373x193mm / 9kg
cooling	convection
working temperature	-10°C to 40°C
IP rating	IP65

